



Angle & Vertical Grinders

4" & 5" Right Angle Grinders



- Lightweight aluminium housing to help reduce operator fatigue.
- Designed to handle a variety of applications from fine deburring to heavy grinding.



519



911



- Ergonomic cushion grip handle for greater comfort and minimal vibration.
- Swivel side exhaust directs exhaust air away from work area.
- Stall torque resistance superior than regular tools and out performs the competition.
- Powerful twin chamber motor for higher torque and working efficiency.



5190



9110



- Excellent power-to-weight ratio.
- Non friction governor system allows constant grinding performance.



SG-414A



SG-511A

Specifications:

Model	Speed (rpm)	Wheel Size (in.)	Spindle Thread	Aver. Air Consumption (cfm)	Length (in.)	Weight (lbs.)	Air Inlet (NPT)	Hose Size (ID)
519	11,000	4" Type 27	3/8"-24	6	9	4	1/4"	3/8"
911	11,000	5" Type 27	5/8"-11	6	10-1/4	4-2/5	1/4"	3/8"
5190	11,000	4" Type 27	3/8"-24	5	9-3/5	3-1/3	1/4"	3/8"
9110	10,000	5" Type 27	5/8"-11	5	9-3/5	3-1/3	1/4"	3/8"
SG-414A	13,600	4" Type 27	3/8"-24	34	9-11/16	2-9/10	1/4"	3/8"
SG-511A	10,900	5" Type 27	5/8"-11	34	9-11/16	3-1/10	1/4"	3/8"

Angle Grinders

4" 4-1/2" & 5" Angle Grinders



- Industrial
- Vibration Reduced Handle
- Spindle Lock
- Rear Exhaust
- Low Noise - (83 dBA)
- Accepts Type 1 Cut-off and Type 27 grinding wheels.
- Safety Throttle Lever
- Optional Piped Away Exhaust.

Swivel Guard, adjustable in nine(9) steps.



Ergonomic



6192

Specifications:

Model	Speed (rpm)	Wheel Size (in.)	Spindle Thread	Aver. Air Consumption (cfm)	Length (in.)	Weight (lbs.)	Air Inlet (NPT)	Hose Size (ID)
6192-4-1/2	10,000	4-1/2	5/8"-11	4	9.4	4.4	1/4"	3/8"
6192-5	10,000	5	5/8"-11	4	9.4	4.4	1/4"	3/8"



- Super Duty Industrial
- Stainless steel extra strong right-angle head, resists corrosion.
- Taller gears provide more power at a lower rpm.
- Spiral-bevelled gears provide smooth operation and longer life.
- Removable side handle. ■ Aluminum or steel case.
- Adjustable side exhaust. ■ U.S. made.

Standard Equipment - 4" Guard, wrenches, wheel washers, spindle nut, side handle, screen bushing. For a steel model, add a "S" to end of model number. For a 5/8"-11 spindle, change "1" to "2".



44RA1K

Specifications:

Model	Exhaust Direction	Throttle Type	Case Material	Weight (lbs.)	CFM	Spindle Thread & Length	Rated Speed / Guard Size
44RA1K;11000;427	Front or Side	Safety	Steel or Aluminum	2.8 Alum. 3.5 Steel	25	3/8"-24 x 0.580" (14.7mm)	11,000 rpm w/ 4" T27 Wheel Guard



The **GA-1340** and **GAL-1340** style Type 27 depressed centre grinders are also available in a Type 1 wheel design. The spindle has been lengthened to allow a Type 1 wheel with a maximum width of 1/4". For those tight spaces, when cutting or edge grinding is required. Industrial applications include foundries, welding shops, fabrication plants, steel mills and shipyards.

- Heavy duty 1 hp motor. ■ Optional lockout lever available.
- Spiral bevel gears. ■ Side exhaust with adjustable deflector.
- Small head for easy accessibility to tight work surfaces. ■ U.S. made.
- Interchangeable motor parts with all 1340 series grinders.



GA-1340



GAL-1340

Specifications:

Model	Speed (rpm)	Throttle Type	Spindle Thread	Wheel Size	Length (in.)	Weight	Housing Type	Air Inlet (NPT)
GA-1340-4	13,500	Lever Self Closing	3/8"-24	4"	8	3 lbs. 2 oz.	Steel	1/4"
GAL-1340-4	13,500		3/8"-24	4"	10	3 lbs. 8 oz.	Steel	1/4"

Angle Grinders

4" & 5" Right Angle Grinders



Patco GA-11650 Grinders designed for applications that other grinders cannot handle, spiral bevelled gears and a wick type lubricating system delivers the durability you need in the most challenging of conditions. Uses - grinding, deburring and blending. Industrial applications include foundries, welding shops, fabrication shops, steel mills and shipyards.

- Dead handle for added stability and leverage.
- Heavy duty 1 hp motor.
- Side exhaust with adjustable deflector.
- Interchangeable motor parts with all 1340 series.
- U.S. made.



GA-11650

Specifications:

Model	Speed (rpm)	Wheel Size (in.)	Spindle Thread	Length (in.)	Weight (lbs.)	Air Inlet (NPT)
GA-11650-3/8	11,000	4	3/8"-24	7-1/2	5	1/4"
GA-11650	11,000	5	5/8"-11	7-1/2	5	1/4"

7" Right Angle Grinders



- Lightweight aluminium housing to help reduce operator fatigue.
- Designed to handle a variety of applications from fine deburring to heavy grinding.
- Equipped for Type 27 depressed centre wheels.



831-L



- Excellent power-to-weight ratio.
- Non friction governor system allows constant grinding performance.



SG-776A

Specifications:

Model	Speed (rpm)	Wheel Size (in.)	Spindle Thread	Aver. Air Consumption (cfm)	Length (in.)	Weight (lbs.)	Air Inlet (NPT)	Hose Size (ID)
831-L	7,000	7	5/8"-11	6.5	13-1/2	8	1/4"	3/8"
SG-776A	7.600	7	5/8"-11	57	11-13/16	6-2/5	3/8"	1/2"

Angle Grinders

7" Right Angle Grinder



Top Cat Large Right Angle Wheel Grinder -

- Spindle Lock Mechanism (Standard)
- 2 hp motor.
- Dual Position Dead Handle
- Equipped for Type 27 depressed Centre, Cut-off. ■ U.S. made.



520RAK1

Standard Equipment - Movable Dead Handle.

Specifications:

Model	Speed (rpm)	Wheel Size (in.)	Spindle Thread	Aver. Air Consumption (cfm)	Length (in.)	Weight (lbs.)	Air Inlet (NPT)	Hose Size (ID)
520RAK1;10000;727	10,000	7	5/8"-11	40	15	8	1/2"	1/2"

Vertical Grinders



These **TopCat** Vertical Grinders are lightweight and easy to maneuver. Ideal for use with depressed centre grinding wheels, wire brushes, cup grinding wheels, and sanding discs.

- Corrosion resistant stainless steel governor keeps the tool at a steady rpm, while maintaining maximum power.
- Lightweight high-alloy aluminum housing, heat-treated for long service.
- Two position "dead" handle adjusts to 90° or 120° for best control.
- U.S. made.

Standard Equipment: 6", 7", or 9" Guard. 1" - 2" wheel flange wrench, 1 - spindle nut.

Wheel Kit sold separately. Other speeds available by special order.

7" & 9" Vertical Grinders



**54VK
64VK**

6" Vertical Cup Grinders



**58CK
68CK**

Specifications:

Model	Throttle Type (Lever)	Rated Power	Weight	Height to Bottom of Flange	Air Consumption	Speed - Wheel Size/Type
54VK;6000;727	Safety	3 hp	8.8 lbs.	6.63"	45 cfm	6,000 rpm w/ 7" T27 Wheel Guard
54VK;6000;927	Safety	3 hp	8.8 lbs.	6.63"	45 cfm	6,000 rpm w/ 9" T27 Wheel Guard
58CK;6000;611	Safety	3 hp	8.8 lbs.	7.06"	45 cfm	6,000 rpm w/ 6" T6 or T11 Wheel Guard
64VK;6000;727	Safety	4 hp	11 lbs.	7.30"	50 cfm	6,000 rpm w/ 7" T27 Wheel Guard
64VK;-6000;927	Safety	4 hp	11 lbs.	7.30"	50 cfm	6,000 rpm w/ 9" T27 Wheel Guard
68CK;6000;611	Safety	4 hp	11 lbs.	7.74"	50 cfm	6,000 rpm w/ 6" T6 or T11 Wheel Guard



Just Tools Inc.

33A Haas Road, Toronto, On M9W 3A1
 Tel: 416-748-0707 Toll Free: 1-888-748-0707
 Fax: 416-748-0706 E-mail: sales@justtools.com
www.justtools.com