



Screwdrivers



1/4" Direct Drive Screwdrivers

Composite Housing Screwdrivers

- Quick change bit holder.
- Top mount reverse valve - Easy to switch direction - One hand.
- Low Noise 72 - 76 dBA
- Powerful 7 Vane Motor
- Output power 30% more than other models.
- **Lightweight, Ergonomic easy grip.**
- For a wide variety of soft draw applications i.e. wood, self tapping or trim screws.



NEW!

A39BPD - \$180.00

A58BPD - \$270.00



- Ball bearing construction.
- Muffled handle for quiet operation.
- New rubber grip handle.
- Planetary gearing.
- Variable speed trigger.



8704 - \$189.00



8705 - \$124.00



1/4" Impact Clutch Screwdrivers

- These Screwdrivers offers quick and powerful operation in driving screws and removing work for highest productivity. The Quick-change hex collet allows instant change of bit for easier and smooth assembly, specially designed for industrial use.



**6SLD
\$398.00**



**6SSLD
\$398.00**

Specifications:

Also available in 3/8" square drive.

Model	Speed (rpm)	Bit Size (in.)	Air Inlet (NPT)	Air Pressure (psi)	Aver. Air Consumption (cfm)	Torque (in./lbs.)	Length (in.)	Weight (lbs.)	Hose Size (ID)
A39BPD	1,600	1/4	1/4"	90	5	44	5-1/2	1.1	3/8"
A58BPD	750	1/4	1/4"	90	9.5	115	6-1/3	1.6	3/8"
8704	800	1/4	1/4"	90	4	145	7	3	3/8"
8705	1,800	1/4	1/4"	90	4	115	6-1/2	4	3/8"
6SLD	7,300	1/4	1/4"	90	10.5	50	6-7/8	2-1/5	3/8"
6SSLD	7,300	1/4	1/4"	90	10.5	50	7-61/64	2	3/8"

All Screwdrivers - 1/4" Hex Power Bit.

Screwdrivers



1/4" Positive Clutch Screwdrivers

Composite Housing Screwdrivers

- **Lightweight**, Ergonomic easy grip.
- Powerful 7 Vane Motor.
- Output power 30% more than other models.
- Top mount reverse valve - Easy to switch direction - One hand.
- Low Noise 72 - 76 dBA.



A39PS - \$185.00
A58PS - \$275.00



- Top mount reverse valve.
- Ergonomic handle design.
- Variable speed tease throttle.
- Built-in comfort grip.



8140 - \$145.00



8160 - \$160.00



1/4" Adjustable Clutch Screwdrivers

Composite Housing Screwdrivers

- Quick change bit holder.
- Powerful 7 Vane Motor
- Output power 30% more than other models.
- Low vibration clutch
- **Lightweight**, Ergonomic easy grip.
- External Clutch Adjustment.
- Top mount reverse valve - Easy to switch direction - One hand.
- Low Noise 72 - 76 dBA.



A39BPN - \$275.00
A58BPN - \$289.00

Specifications:

Model	Speed (rpm)	Bit Size (in.)	Air Inlet (NPT)	Air Pressure (psi)	Aver. Air Consumption (cfm)	Torque (in./lbs.)	Length (in.)	Weight (lbs.)	Hose Size (ID)
A39PS	1,600	1/4	1/4"	90	5	44	5-1/2	1-1/3	3/8"
A58PS	750	1/4	1/4"	90	9.5	115	6-1/2	2	3/8"
8140	1,800	1/4	1/4"	90	4	115	7	2-1/3	3/8"
8160	800	1/4	1/4"	90	4	145	8-1/2	2-2/3	3/8"
A39BPN	1,600	1/4	1/4"	90	5	4.5 - 35	5-1/2	1-1/3	3/8"
A58BPN	750	1/4	1/4"	90	9.5	9 - 79	6-1/2	2	3/8"

All Screwdrivers - 1/4" Hex Power Bit.

Screwdrivers



1/4" Adjustable Clutch Screwdrivers

- Top mount reverse valve.
- Ergonomic handle design.
- Variable speed tease throttle.
- Built-in comfort grip.



8120 - \$189.00



8130 - \$209.00



842 - \$171.40



843 - \$192.32



- Excellent power-to-weight ratio, handles tough jobs with minimal operator fatigue.



1/4" Auto Shut-Off Screwdrivers

Composite Housing Screwdrivers

- Air Motor will automatically stop when the load reaches the pre-set torque. Torque accuracy repeatable to + / - 3%.
- Powerful 7 Vane Motor
- Output power 30% more than other models.
- **Lightweight, Ergonomic easy grip.**
- Push-to-Start system. (Pistol Grip Push-to-Start Lever Permit).
- Trigger Lock feature. (Pistol only)
- Top mount reverse valve - Easy to switch direction - One hand.
- Low Noise 72 - 76 dBA
- External Clutch Adjustment.
- Torque Adjusting Cover c/w Tool.



A55PBP - \$650.00

A60PBP - \$650.00



A55BP - \$588.00

A60BP - \$588.00

Specifications:

Model	Speed (rpm)	(in.)	Air Inlet (NPT)	Air Pressure (psi)	Aver. Air Consumption (cfm)	Torque (in./lbs.)	Length (in.)	Weight (lbs.)	Hose Size (ID)
8120	1,800	1/4	1/4"	90	4	45 - 115	7	2-1/3	3/8"
8130	800	1/4	1/4"	90	4	45 - 145	8-1/2	2-2/3	3/8"
842	1,800	1/4	1/4"	90	4	45 - 115	10	2-1/2	3/8"
843	800	1/4	1/4"	90	4	45 - 145	11	2-2/3	3/8"
A55PBP	1,000	1/4	1/4"	90	9.5	11 - 65	10	2	3/8"
A60PBP	550	1/4	1/4"	90	9.5	26 - 95	10	2	3/8"
A55BP	1,000	1/4	1/4"	90	9.5	6 - 56	8-1/2	1-3/4	3/8"
A60BP	550	1/4	1/4"	90	9.5	13 - 82	8-1/2	1-3/4	3/8"

All Screwdrivers - 1/4" Hex Power Bit.

Screwdrivers



1/4" Auto-Shut-Off DC Electric Screwdrivers

- Low torque range starting from .44 in/lbs (0.05 NM),
- Ergonomic design, lightweight, small diameter (1.16") for operator comfort.
- High quality motor with fan and vent for fast motor cooling.
- For use in electronics assembly, circuit boards, computer hardware etc. any application needing precise repeatable low torque assembly.
- Optional torque adjustment cover to avoid accidental torque changes. ■ All models CUL approved.

SKD-2200 \$440.00



SKD-5200 \$440.00



SKD-1 (Single Output) & SK-DU2 (Double Output) DC Screwdriver Power Supplies

\$150.00



\$300.00



Power Supply for the **SKD-2200** and **SKD-5200**. **SKD-1** runs one tool. **SK-DU2** runs two tools.

KC-1 Torque Cover

\$22.50

Optional torque adjustment cover to avoid accidental torque changes. For series **SK & SKD** Screwdrivers.



1/4" Auto-Shut-Off AC Electric Screwdrivers

- Adjustable Precision auto shut-off clutch.
- Fully adjustable torque settings throughout entire range.
- Optional cover stops accidental torque adjustment.
- External torque adjustment for easy set up.
- Pistol Grip can be added if needed (**PG**).
- Uses standard 1/4" hex power bits. CUL approved.



Shown with "PG" Pistol Grip

SK-9130PB - \$560.00

SK-9140PB - \$560.00

SK-9150PB - \$590.00

KTM-100 - Torque Tester \$2,525.00

Ideal for testing output torque of assembly tools up to 100 in/lbs. in calibration labs, repair crib or on the production line. Charging time is less than 8 hours. 12-30 hours continuous working time.



c/w Metal Carrying Case

PG Pistol Grip

\$19.75

Attachment for the **SK-9130PB**, **SK-9140PB** and **SK-9150PB** Electric Screwdrivers.



Specifications:

Model	SKD-2200	SKD-5200	SK-9130PB	SK-9140PB	SK9150PB
Input Voltage	DC 24V or 32V		AC 110~120V 50 / 60 Hz.		
Torque - N.m	.05 - .69	.10 - 1.18	.49 - 2.16	.98 - 2.94	1.47 - 4.41
Torque - in./lbs.	.44 - 6.16	.88 - 10.56	4.4 - 19.36	8.8 - 26.4	13.2 - 39
Torque Adjustment	Stepless				
Free Speed (rpm)	700 / 1,000	700 / 1,000	1,000	700	500
Weight (g/lbs.)	270 / .59		480 / 1.05		
Length (mm/ins.)	205 / 8.07		230 / 9.05		
			269 / 10.59		

All Screwdrivers - 1/4" Hex Power Bit.
Repeatable Torque Accuracy - + / - 3 %



Just Tools Inc.

33A Haas Road, Toronto, On M9W 3A1
Tel: 416-748-0707 Toll Free: 1-888-748-0707
Fax: 416-748-0706 E-mail: sales@justtools.com
www.justtools.com